MASTER COPY KEEP THIS COPY FOR REPRODUCTION PURPOSES

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED
	3 July 1997	Final

4. TITLE AND SUBTITLE
Work Shop on Applications and Research Strategies for Quasi-Optical Power Combining

5. FUNDING NUMBERS
DAAH04-95-1-0622

6. AUTHOR(S)
Dr. James W. Mink
Dr. Michael Steer

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)
North Carolina State University
Department of Electrical and Computer Engineering
Room 232 Daniels Hall
Raleigh, NC 27695-7911

8. PERFORMING ORGANIZATION REPORT NUMBER

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)
U.S. Army Research Office
P. O. Box 12211
Research Triangle Park, NC 27709-2211

10. SPONSORING / MONITORING AGENCY REPORT NUMBER
ARO 35008.1-EL-CF

11. SUPPLEMENTARY NOTES
The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.

12a. DISTRIBUTION / AVAILABILITY STATEMENT
Approved for public release; distribution unlimited.

12b. DISTRIBUTION CODE

13. ABSTRACT *(Maximum 200 words)*

To assemble key researchers in the field of quasi-optical power combining, along with principal representatives of industry and the government who would have potential applications for this technology. To discuss the prospects for military and commercial applications of quasi-optical power combining. To identify key technical issues remaining to be resolved for system application.

DTIC QUALITY INSPECTED 4

14. SUBJECT TERMS

15. NUMBER OF PAGES

16. PRICE CODE

17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
UNCLASSIFIED	UNCLASSIFIED	UNCLASSIFIED	UL

NSN 7540-01-280-5500

Standard Form 298 (Rev 2-89)
Prescribed by ANSI Std 239-18
298-102

WORKSHOP ON APPLICATIONS AND RESEARCH STRATEGIES

FOR

QUASI-OPTICAL POWER COMBINING

Dr. James W. Mink

3 July 1997

U.S. ARMY RESEARCH OFFICE

DAAH04-95-1-0633

35008-EL-CF

NORTH CAROLINA STATE UNIVERSITY

DEPARTMENT OF ELECTRICAL AND COMPUTER ENGINEERING

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

19970818 086

FINAL REPORT

WORKSHOP ON APPLICATIONS AND RESEARCH STRATEGIES FOR QUASI-OPTICAL POWER COMBINING

WORKSHOP OBJECTIVES

To assemble key researchers in the field of quasi-optical power combining, along with principal representatives of industry and the government who would have potential applications for this technology. To discuss the prospects for military and commercial applications of quasi-optical power combining. To identify key technical issues remaining to be resolved for system application.

DATE AND LOCATION OF WORKSHOP

The workshop was held on December 4, 1995 in Raleigh, North Carolina at the Brownstone Hotel.

WORKSHOP AGENDA

The workshop followed the agenda given below:

0830 Welcome
0845 Meeting Objectives
0900 State of the Art of Quasi-Optical Combining and University Research
1000 Industry Issues for Application of Quasi-Optical Devices, Systems
1100 Military System Issues for Application of Quasi-Optical Techniques
1200 Lunch
1300 Panel Discussion with Industry / Military / University Experts
1400 Panel Deliberations (Open to panel members only)
1530. Presentation of Panel Findings to Director of the Army Research Office

WORKSHOP PANEL MEMBERS AND ATTENDEES

Panel Members:

L. Brockman	Lockheed Martin	
W. Gelnovatch	Army Research Laboratory	(Panel Chair)
W. Carroway	Army Missile Command	
P. Greiling	Hughes Research Laboratory	
D. Westervelt	Harvard University	
W. Kornegay	MIT/Lincoln Laboratory	
M. Stroscio	ARO	
E. Reedy	Ga. Tech.	

Attendees:

J. Mink	NCSU
M. Steer	NCSU
J. Harvey	ARO
D. Rutledge	Cal. Tech.
Z. Popovic	Univ of Colorado
T. Itoh	UCLA
F. Schwering	CECOM
B. Perlman	USARL
R. York	UC Santa Barbara

CONCLUSION OF WORKSHOP

As indicated by the agenda, the state-of-the-art quasi-optical techniques was presented by university and industrial representatives. This was followed by open discussion. General conclusion of the workshop was that quasi-optical techniques hold promise for the generation of large power levels at millimeter wavelengths. All presentation material is attached.

Much research to date focused upon self-oscillating technique which demonstrated that significant power could be generated in the microwave region of the EM spectrum. A significant result of this workshop was that military and potential industrial systems require amplifying systems. This requirement is a result of advanced signal processing techniques utilized by current systems and the need for low noise.

From the technical point of view, concerning quasi-optical systems, two major issues were determined. First, that with the complexity and close coupling of many active devices, further advancements will require the development of computer aided tools to design such systems. The systems are just to complex and cover a wide spectrum of techniques to be resolved through analytical techniques alone. The second major finding of the workshop was that thermal problems may limit the overall performance of quasi-optical systems. Since, the active devices will be embedded in large arrays and because of electromagnetic considerations, they may not have adequate heat removal. This is an issue that must be addressed and further research is required.

At the request of the sponsor, the panel conclusions are not known to the author since the panel provided its recommendations directly to Dr. Iafrate, Director, Army Research Office and they were not made public.

J. Mink

M. Steer

MAR 15 1996

AN OVERVIEW OF QUASI-OPTICAL POWER COMBINING: WHERE WE ARE AND HOW WE GOT THERE

JAMES W. MINK / M. STEER
NORTH CAROLINA STATE UNIVERSITY

MAR 05 1996

OUTLINE OF PRESENTATION

- RELATIONSHIP TO MICROWAVES / OPTICS
- WHY QUASI-OPTICAL TECHNIQUES
- METHODS OF FEEDBACK
- FAMILIES OF QUASI-OPTICAL APPROACHES
- STATE-OF-THE- ART
- CONCLUSIONS

MAR 13 1995

WHY QUASI-OPTICAL DEVICES

- TO COMPENSATE FOR THE $1/f^2$ PROBLEM ASSOCIATED WITH ACTIVE DEVICES
- TRANSVERSE DIMENSIONS RANGE FROM 10 TO 100 WAVELENGTHS
- RELAXED LONGITUDINAL BOUNDARY CONDITIONS
- EASILY FABRICATED LENSES AND REFLECTORS
- SUBSTANTIAL TRANSVERSE "REAL-ESTATE"
- MANY ACTIVE ELEMENTS MAY BE UTILIZED

MAR 05 1996

MILLIMETER WAVE SOURCE STATE OF THE ART



MAR 05 1996

SIMILARITY TO THE LASER

- MANY LOW POWER SOURCES ACTING COHERENTLY
- SOURCES MAY BE DISTRIBUTED THROUGH OUT THE VOLUME
- OUTPUT POWER IS IN THE FORM OF A BEAM
- "FABRY-PEROT" RESONATOR
- HIGH SPECTRAL PURITY

COMPARISON TO LASER



Similarity of Quasi-Optical Technique to Gas Laser

MAR 15 1996

Types of quasi-optical sources



MAR 05 1996

CLASSES OF QUASI-OPTICAL OSCILLATORS: I

- OPEN RESONATOR OSCILLATORS
  - HIGH Q STRUCTURES
  - FEED-BACK VIA ELECTROMAGNETIC WAVE-BEAM MODES

MAR 15 1996

OPEN RESONATOR CONFIGURATION



MAR 1996

CLASSES OF QUASI-OPTICAL OSCILLATORS: II

- GRID SYSTEMS
  - LOW Q STRUCTURE
  - PRIMARY FEED-BACK VIA TRANSMISSION LINE COUPLING
  - SECONDARY FEED-BACK VIA ELECTROMAGNETIC WAVE-BEAM MODE
  - INPUT / OUTPUT ISOLATION VIA ORTHOGONAL POLARIZATION

MAR 05 1996

GRID OSCILLATOR CONFIGURATION





MAR 05 1996

CLASSES OF QUASI-OPTICAL OSCILLATORS: III

- SLAB WAVE-BEAM RESONATORS
  - MODERATE TO HIGH Q STRUCTURE
  - FEED-BACK VIA ELECTROMAGNETIC WAVE-BEAM
  - "PLANAR STRUCTURE"
  - TRAVELING WAVE AMPLIFICATION

MAR 15 1996

SLAB-RESONATOR CONFIGURATION





MAR 05 1996

REPORTED QUASI-OPTICAL SOURCES

FREQ (GHz)	ARRAY SIZE	DEVICE TYPE	POWER (mW)	REFERENCE
5.0	10X10	FET	550	Rutledge, et.al.
7.3	3X3	FET	282	Mortazawi, et.al
8.2	4X4	FET	184	York, et.al.
9.8	10X10	FET	10300	Rutledge, et.al.
34.7	6X6	HBT	-	Kim, et.al.
37	4X4	HEMT	-	Wiltse, et.al.
60	2X4	IMPATT	2200	Compton, et.al.

Power pkg effects ~ 20%

MAR 05 1996

CONCLUSIONS

- QUASI-OPTICAL OSCILLATORS HAVE BEEN DEMONSTRATED IN EACH CLASS
- EMPHASIS HAS SHIFTED TO THREE TERMINAL ACTIVE ELEMENTS FOR BOTH SOURCES AND AMPLIFIERS
- IMPEDANCE MATCHING FOR MAXIMUM OUTPUT POWER REMAINS A PROBLEM
- CAD TOOLS ARE UNDER DEVELOPMENT AND ARE ESSENTIAL

MAR 05 1996

TWO DIMENSIONAL QUASI-OPTICAL POWER COMBINING FOR MILLIMETER-WAVE COMMUNICATIONS

M. B. Steer

Electronics Research Laboratory
North Carolina State University

mbs@ncsu.edu 919-515-5191

Outline

- Overview of Quasi-Optical Power Combining
- Two-Dimensional Quasioptical Power Combining System
- A Quasi-Optical 2D Power Combining Oscillator
- A Quasi-Optical 2D Power Combining Amplifier
- Future Directions and Needs of Quasioptical Power Combining
  What is required to make active quasi-optics a military/commercial reality

Contributors

MAR 15 1996

C. Hicks, S. Irrgang, S. Zeisberg, A. Schuenemann,
T. Nutesson, G. P. Monahan H. Hwang, J. W. Mink
Electronics Research Laboratory North Carolina State University

F. K. Schwering U.S. Army CECOM

A. Paolella U.S. Army Research Laboratory
J. Harvey U.S. Army Research Office

ALSO
D. Rutledge, Z. Popovic, R. York, A. Mortazawi

Applications

Where Ever You Need More Power than Can be Obtained From A single Solid-State Device

1. Near Vehicle Detection Radar (Collision Avoidance Radar)
2. Millimeter-Wave LAN's (e.g. 60 GHz)
3. Cellular Radio Base Stations
4. Active Missile Seekers
5. Millimeter-Wave Imaging (100+ GHz) Detection of Plastics

MAR 15 1996

Free Space Combining



Open Cavity Resonator



2D Power Combiner



Grid



CAE Issues

1. Handling Device-Field Interactions in a Non-Planar Environment.
   — Modeling Paradigm
   — DC-to-Daylight Modeling
2. Handling a Very Large Number of Active Devices in Steady-State Harmonic Balance Analysis.
3. Optimization in Design Requires Steady-State Methods.
4. Handling Distributed High Q Passive Components in Transient Analysis. Turn-on Stability is a major concern.
5. Wholistic Approach required to Achieve High Efficiencies.

MAR 05 1996

2D Power Combining Oscillator

Spectrum With Four Oscillators

Oscillators Biased One at a Time



MAR 05 1996

2D Power Combining System



Quasi-Optical Dielectric 2D Amplifier System



2D Dielctric Quasioptical Power Combining System

MAR 15 1996



- Resonant Cavity Oscillator Development
- Amplifier/Tripler Array Development
- Lens Development
- Leaky-Wave Antenna Development
- Circuit Model/CAE Tool Development

Amplifier Array in the 2D Dielectric Waveguide



Amplifier with FET

MAR 05 1996



FET ampilifier

Phase Transformer: Convex and Concave Lenses



MAR 05 1996

Structure of Concave Lens.



2D Dielectric Leaky-Wave Antenna Structures.



MAR 25 1996

Quasi-Optical 2D Oscillators.



The 2-D System With Convex/Concave Lenses



MAR 15 1996

Amplifer Array Underneath The Slab



Passive System Gain (No Amplifiers In The System)



MAR 05 1996

Insertion Loss Of Amplifiers Inside System



$|Ey|$ Patterns Before and After The Lenses



MAR 05 1996

The 2-D system with A Metallic Top



Amplifier Gains in Convex/Concave-Lens System



MAR 05 1996

Active System Gains W/ and W/O A Metallic Top



P_{out} V.S. P_{in} W/O A Metallic Top



P_{out} V.S. P_{in} W/ A Metallic Top

MAR 05 1996



Additive Amplification





Measured $|Ey|$ Near The Receiving Horn

MAR 5 1996



Summary

- A Viable Method of 2D Quasi-Optical Power Combining Has Been Demonstrated
- Amenable to Fabrication Using Photolithographic Techniques and MMIC Technology
- Smaller Size Because of Dielectric
- No Significant Thermal Dissipation Problem
- Resistive Driving Point Impedance Greater Than for Open-Cavity Structures

... Summary

MAR 1996

Requirements:

- Circuit Model/CAE Tool Development
- Development of a calibrated measurement system
- Development of analytic and numerical techniques
- The Lack of Computer Aided Engineering Tools is the Major Impediment to the Development of Quasi-Optical Systems
- Field Analysis Tools

- Transient Analysis (Spice)
- Steady State Analysis (Harmonic Balance)
- In the U.S. addressed by two Small Business Innovative Research Programs
  - MICOM/USARO *Scientific Research Associates*
    working with North Carolina State University
    Custom Quasi-Optical Tools
  - ARPA *Compact Software*
    working with University of Colarado at Boulder & North Carolina State University
    Augmentation of Existing Tools

MAR 15 1996

Acknowledgement

The work is supported by the U.S. Army Research Office
DAAL04-95-1-0536, Dr. James Harvey, program manager.

ELECTROMAGNETIC MODELING OF QUASI-OPTICAL POWER COMBINERS

Todd W. Nuteson

Ph.D. Preliminary Oral Exam
April 1, 1996
10:00 am, 406 Daniels Hall

Electronics Research Laboratory
North Carolina State University

Outline

- Overview of Quasi-Optical Power Combining
- Electromagnetic Modeling
  - Quasi-Optical Green's Functions
  - Method of Moments (MoM)
- Quasi-Optical Systems
  - Open Cavity Resonator
  - Grid Amplifier System
- Summary

Cascaded Oscillator and Amplifier Power Combiner



CAE Tool Development

- The Lack of Computer Aided Engineering Tools is the Major Impediment to the Development of Quasi-Optical Systems
- Development of Analytic and Numerical Techniques
  - Field Analysis Tools
  - Transient Analysis (Spice)
  - Steady State Analysis (Harmonic Balance)

Open Cavity Resonator Dyadic Green's Function



$$\bar{\bar{G}}_E = \bar{\bar{G}}_{Eh} - \sum_{m=0}^{Nm}\sum_{n=0}^{Nn} \frac{R_{mn}\psi_{mn}}{2(1+R_{mn}\psi_{mn})} \cdot \left[E^-_{mn} - E^+_{mn}\right]\left[\acute{E}^-_{mn} - \acute{E}^+_{mn}\right] \bar{\bar{I}}_t$$

Lens System Dyadic Green's Function



$$\bar{\bar{G}}_E = \bar{\bar{G}}_{E0} - \sum_{m=0}^{Nm}\sum_{n=0}^{Nn} \frac{R_{mn}\psi_{mn}}{(1-R_{mn}\psi_{mn})} E_{mn}\acute{E}_{mn} \bar{\bar{I}}_t$$

Reflection Coefficient

Magnitude:

$$R_{mn} = \Gamma \, \alpha_{d,mn}$$

Γ $\Rightarrow$ reflection coefficient of lens

$\alpha_{d,mn}$ $\Rightarrow$ diffraction losses

Phase:

$$\psi_{mn} = \frac{E^{+}_{mn}(x,y,D)}{E^{-}_{mn}(x,y,D)}$$

good approximation at $x = y = 0$

Test Fields



$$\mathbf{E}_{T,st} = \begin{cases} a_{st} E^{-}_{st} \, \hat{\mathbf{a}}_x & , \quad z < -D \\ \left(c_{st} E^{+}_{st} + b_{st} E^{-}_{st}\right) \hat{\mathbf{a}}_x & , \quad -D < z < D \\ \left(d_{st} E^{+}_{st} + E^{-}_{st}\right) \hat{\mathbf{a}}_x & , \quad z > D \end{cases}$$

with boundary conditions (R_{mn}, T_{mn}) at each lens, unknown coefficients can be solved

Modal Component

$$\bar{\bar{G}}_{Em} = -\sum_{mn} \frac{\acute{E}_{mn}}{2(1 - R_{mn}\psi_{mn})} \bar{\bar{I}}_t$$

$$\begin{cases} T_{mn}E^-_{mn} & , \quad z < -D \\ (R_{mn}\psi_{mn}E^+_{mn} + E^-_{mn}) & , \quad -D < z < 0 \\ (E^+_{mn} + R_{mn}\psi_{mn}E^-_{mn}) & , \quad 0 < z < D \\ T_{mn}E^+_{mn} & , \quad z > D \end{cases}$$

Paraxial Component

determined from $\bar{\bar{G}}_{Em}$ with $R_{mn} \to 0$ and $T_{mn} \to 1$



$$\bar{\bar{G}}_{Ep} = -\frac{1}{2}\sum_{mn} \acute{E}_{mn} \bar{\bar{I}}_T \begin{cases} E^-_{mn} & , \quad z < 0 \\ E^+_{mn} & , \quad z > 0 \end{cases}$$

Electric Field Integral Equation & MoM

Total Tangential Electric Field on Conductor Surface is Zero:

$$-\mathbf{E}_t^{scat}(x,y) = \mathbf{E}_t^{inc}(x,y)$$

Scattered Electric Field Relationship to Dyadic Green's Function:

$$\mathbf{E}_t^{scat}(x,y) = \int_{y'}\int_{x'} \overline{\overline{\mathbf{G}}}_E \cdot \mathbf{J}_S(x',y')\,dx'dy'$$

Current Density Expanded in a Set of N Basis Functions:

$$\mathbf{J}_S(x',y') = \sum_{i=1}^{N} I_i \mathbf{W}_i(x',y')$$

Expansion and Testing (Galerkin Method) Yield Matrix Equation:

$$[\mathbf{Z}][\mathbf{I}] = [\mathbf{V}]$$

Solve for Unknown Currents I_i

Sub-Domain Sinusoidal Basis Functions





$$W_i^x(x) = \begin{cases} \dfrac{\sin\left[k_0\left(a - |x - x_i|\right)\right]}{b\sin\left(k_0 a\right)} & , \quad |x - x_i| \le a \\ 0 & , \quad \text{otherwise} \end{cases} \quad |y - y_i| \le b/2$$

Excitation Vector Elements

$$V_j = \int_y \int_x \mathbf{W}_j(x,y) \cdot \mathbf{E}_t^{inc}(x,y)\, dx\, dy$$

- Incident Field Produced From:
  - Coaxial Current Probe
  - Delta-Gap Voltage Generator
  - Incident Plane-Wave
  - Incident Gaussian Beam-Mode

Method of Moments Flowchart



Driving Point Impedance of the Inverted L Antenna

$TEM_{0,0,35}$ mode





solid line: MoM simulation

dashed line: measurement

Driving Point Impedance of the Inverted L Antenna

$TEM_{0,1,35}$ and $TEM_{1,0,35}$ modes





solid line: MoM simulation

dashed line: measurement

Driving Point Impedance of the Patch Antenna

half-space



solid line: MoM simulation
dashed line: measurement

cavity

$D = 62.05cm$



solid line: $TEM_{0,0,34}$ mode
dashed line: $TEM_{0,0,23}$ mode

Cavity Field Effects of the Patch Antenna

cavity resonant mode frequencies $f_{m,n,q}$



MoM simulation

solid line: antenna in cavity

dashed line: antenna in half-space

Cavity Field Effects of an IMPATT Diode Oscillator

$D = 61.25cm$ $D = 61.4cm$



solid line: oscillator in half-space dashed line: oscillator in cavity

dotted line: MoM simulated scaled reflection coefficient magnitude

Driving Point Impedance on Expanded Smith Chart

markers show oscillation frequencies

$D = 61.25cm$ $D = 61.4cm$



MoM simulation from 8.63825 GHz to 8.67 GHz

solid line: oscillator in cavity dashed line: oscillator in half-space

3 × 3 Grid Structure with Open Gaps



Driving Point Reflection Coefficient

extended unit cell





solid line: MoM simulation

dashed line: measurement

Driving Point Reflection Coefficient

3×3 grid with other gaps shorted





solid line: MoM simulation

dashed line: measurement

5×5 Grid Structure with Cell Sub-Division



Driving Point Reflection Coefficient

5×5 grid on a dielectric substrate in the lens system
($\epsilon_r = 2.56$, $d = 9.5$ mm, $D = 117.5$ cm)





solid line: MoM simulation

dashed line: measurement

Configuration for Measuring Electric Field Intensity

X Band (8.2 GHz to 12.4 GHz)



horn aperture: 19.5 cm × 14.3 cm

lens material: Rexolite 1422 (ϵ_r=2.56) diameter: 45.72 cm

radius of curvature: 70.49 cm focal length: 58.74 cm

Summary

- Full-Wave Field Analysis Tools Developed for Quasi-Optical Power Combiners
- Incorporates Dyadic Green's Functions Developed for each Quasi-Optical System
- MoM Scheme Utilizing Both Spatial and Spectral Domains for Efficient Computation of the Moment Matrix Elements
- Finite Sized Structures $\Longrightarrow$ No Unit-Cell Approximations
- Accurately Predicts the Driving Point Impedance
- Simulated Results Compare Favorably with Measurements

Acknowledgments

This work was supported in part by the U.S. Army Research Office through grants DAAL03-89-D-0030 and DAAH04-95-1-0536.

Dr. James Harvey, program manager.

MAR 05 1996

Hughes Electronics Quasi-Optical Power Combining Applications

Paul Greiling

Hughes Research Laboratories

Dec.4, 1995

MAR 19 199

Missiles Seeker Radars

- Hughes Missile Systems Company is a major supplier of high performance missiles
- Next generation of Hughes missiles will have more accuracy and longer range, all for a lower cost
- Critical to this next generation missile seeker is a higher power radar operating at a higher frequency

MAR 05 1996

Missile Seeker Radar

- Range increases proportionally to the inverse fourth power of the output power
- Resolution improves linearly with the operating frequency





Missile Seeker Radar Requirements

MAR 05 1996

- Need to increase operating frequency from Ka-band to W-band to D-band
  - New HEMTs
  - Sub-quarter micron gate lengths
- Need to increase output power to watts at millimeterwave frequencies
  - Higher frequency and breakdown voltage devices
  - Power combining techniques

Millimeterwave Device Technology

MAR 05 1996

- Device output power decreases with increasing frequency
- Higher frequency of operation requires shorter gate lengths





MAR 05 1996

Millimeterwave Technologies

- New epitaxial materials systems are required for high power and frequency devices---InP & Sb
- Extremely short gate lengths are required for high frequency operation---<0.1 micron
- Power combining techniques are required for high output power levels---quasi-optical

MAR 05 1998

Radar Cost Drivers

- Cost of high power, high frequency radar is prohibitive due to:
  - semiconductor cost
  - yield
  - power cell size
- Need to combine many low power, low cost devices to achieve high power, high frequency radar



Quasi-optical power combining of low cost cells

TECHNOLOGY COST AND PERFORMANCE

GM HUGHES ELECTRONICS

MAR 05 1996



COMPARISON OF MICROWAVE INTEGRATED CIRCUIT APPROACHES

GM HUGHES ELECTRONICS

9425025016

MAR 05 1996



MONOLITHIC MICROWAVE IC

ADVANTAGES

- LOW ASSEMBLY COSTS

DISADVANTAGES

- LOW YIELD
- HIGH COST FOR NEW TECHNOLOGIES



HYBRID MICROWAVE IC

ADVANTAGES

- LOW COST FOR LOW COMPLEXITY
- DIFFERENT DEVICE TYPES FOR OPTIMIZED PERFORMANCE

DISADVANTAGES

- HIGHER ASSEMBLY COSTS

FLIP-CHIP GRID AMPLIFIER/OSCILLATOR

HUGHES ELECTRONICS

MAR 05 1996



Program Goals

MAR 05 1996

- **Short Term---Yr 2000**
  - **10 Watts @100 GHz for $1000**
- **Long Term---Yr 2005**
  - **100 Watts @ 100 GHz for $100**

Conclusions

MAR 05 1996

- Radar resolution and range must be increased
- Costs must be reduced in the next generation of missile seeker radars
- Trade off of power cell size vs. costs must be performed
- Quasi-optical power combining is required to achieve the desired power levels

mmWave Plane Wave Amplifiers

1996

There are today three monolithic Plane Wave Amplifiers under development at Rockwell Science Center

MAR 05 1996

(a) Grid Amplifier at 40-44 GHz
Uses orthogonally polarized input dipole antennas and output dipole antennas ; developed with Caltech

(b) Slot-Patch PWA at 40-44 GHz
Uses Slot antennas in ground plane of microstrip for input and patch antennas on microstrip surface for output

(c) Folded Slot PWA at 40-44 GHz
Uses orthogonal pairs ofFolded Slot antennas for input and output developed with UCSB

THESE ARE ALL TRANSMISSION TYPE PWAs

Rockwell
Science Center

Monolithic Grid Amplifier

BCRD816A:041395

MAR 05 1996



CALIFORNIA INSTITUTE OF TECHNOLOGY

Rockwell

Science Center

Transmission Amplifiers: Gaussian Power Beam

MAR 05 1996

SC.1125E.040494



Type TGPD1: Power density varies across beam width

Radially non-uniform device sizes to cope with radial power density change

Amplifier diameter increases to accomodate more power

Gaussian optic lenses required for wavefront management

Rockwell International
Science Center

mmWave Plane Wave Amplifiers

MAR 05 1996

A Concept figure illustrating the Guided Wave PWA system



Waveguide is designed to maintain a uniform cross section power density. Three stages of amplification are cacaded in this conceptual sketch

Rockwell

Science Center

PWA Design

MAR 05 1996



Rockwell

Science Center

Plane Wave Amplifier Chip
Mounted on an Aluminum Nitride Carrier

MAR 25 1996





- 44 GHz DWA CELL

Rockwell

Science Center

SCP.0935A090595

Waveguide Test Fixture for mm Wave Plane Wave Amplifier

MAR 15 1996



Rockwell

Science Center

Waveguide Test Fixture for mm Wave Plane Wave Amplifier

MAR 05 1996



Rockwell
Science Center

44 GHz Quasi-Optic PHEMT Amplifier

MAR 05 1996





(Power characteristics of one cell)

- Direct-coupled 2-stage design
  - compact design and good stability

- Small-signal gain > 8 dB
- Total output power ~ 2.2W

Rockwell
Science Center

PHEMT PWA Gain and Return Loss

MAR 05 1996



Max. Output .25W

Measurement is uncorrected for fixture loses. (flange to flange)

Rockwell

Science Center

mmWave Plane Wave Amplifiers

MAR 05 1996

NEXT STEPS

- THE OPTIMUM APPROACH WILL NOT INCLUDE MICROSTRIP PATCH ANTENNAS

  IT WILL BE BASED ON ORTHOGONAL SLOT ANTENNAS FOR INPUT AND OUTPUT BACKED UP BY NEW TECHNOLOGY TO ENHANCE ANTENNA PERFORMANCE:-- PHOTONIC BANDGAP SUBSTRATES

- THE NEW SLOT ANTENNAS MAY BE "FOLDED SLOT ANTENNAS"



Example: Patch antenna

Slot - Slot Unit Cell

MAR 1 6 1996



Rockwell
Science Center

Aluminum Oxide Two Dimensional PBGS
Fabricated Using LOM Rapid Prototyping Technique

MAR 05 1996





Rockwell
Science Center

MAR 05 19

Tranamission through Aluminum Oxide PBGS



mmWave Plane Wave Amplifiers

MAR 1995



The oversized waveguide must have dielectric loading to force field uniformity . Mode control is supplied by properly placed conductor sheets

Rockwell

Science Center

MAR 05 1996

QUASI OPTICAL POWER COMBINING

GOALS:

- Solid-state quasi-optical power amplifiers/sources for 10-100 watts 35 to 100 GHz

- Predictive modeling of device/circuit performance based on full wave analysis of device/antenna array

- Improvement of device (PHEMT) efficiency enabling up to 100 watts at W-band

MAR 15 1996

HIGH POWER MILLIMETER WAVE APPLICATIONS





Path Loss:

$$P_R = P_R G_T G_R \left(\frac{4 \pi r}{\lambda} \right)^2$$

Inter-Sattelite
Communication

Rayleigh Criterion:

$$\theta_{MINIMUM} = 1.22 \frac{\lambda}{D}$$

Hi Resolution
Radar

EXAMPLE OF QUASI-OPTICS

MAR 05 1996

Waveguide Combiner



Quasi-Optical Combiner



Power Combiner Comparison
60 GHz, 0.1W per Element



MAR 05 1996

RADAR SYSTEM REQUIREMENTS AFFECTING QUASI-OPTICAL POWER COMBINING DEVICES

WILL CARAWAY

4 DEC 95

1996

PULSE RADAR BLOCK DIAGRAM



MAR 1995

CONTINUOUS WAVE (CW) RADAR BLOCK DIAGRAM



MAR 1996

GROUND BASED RADAR TRANSMITTER REQUIREMENTS

- TRANSMIT FREQUENCY: 1 - 16 GHz
- OPERATIONAL BANDWIDTH: 200 MHz - 5 GHz
- INSTANTANEOUS BANDWIDTH: 2 MHz - 1 GHz
- TRANSMIT POWER: 1 W - 1 MW
- PHASE NOISE: -50 - -135 dBc/Hz @ 10 kHz (Absolute)
- WAVEFORMS: PULSE, BI-PHASE MODULATED, LINEAR FM, STEPPED FM

MAR 05 1996

RADAR SEEKER TRANSMITTER REQUIREMENTS

- TRANSMIT FREQUENCY: 10 - 95 GHz
- OPERATIONAL BANDWIDTH: 200 - 500 MHz
- INSTANTANEOUS BANDWIDTH: 2 - 500 MHz
- TRANSMIT POWER: 1 - 900 W
- PHASE NOISE: < -120 dBc/Hz @ 10 kHz (Absolute)
- WAVEFORMS: PULSED, LINEAR FM, STEPPED FM

Quasi-Optical Scanned mmW Antennas

MAR 05 1996



MAR 05 1996

UC
SB

Radiatively Coupled Oscillator Arrays

Simple patch-antenna based oscillators synchronized through antenna coupling

Top array: 4x4 Gunn diode array
- **9.6 GHz operation**
- **22 Watts ERP**
- **1% DC-to-RF efficiency**

Bottom array: 4x4 MESFET array
- **8.2 GHz operation**
- **10 Watts ERP**
- **26% DC-to-RF efficiency**

Proof of concept arrays, led to better understanding of coupled-oscillator systems including mutual synchronization, phase dynamics, beam-scanning, and mode-locking





UC SB
University of California, Santa Barbara

Arbitrary Coupling Network

Enforce node coditions:

$$Y_{\text{osc},i}(\omega, V_i) + Y_{\text{circ},i}(\omega, \overline{V}) = 0$$
$$i = 1, 2, \ldots N$$



Convert to dynamic equations (Kurokawa):

$$\omega \Rightarrow \left[\omega_i + \frac{d\phi_i}{dt} - \jmath \frac{1}{A_i}\frac{dA_i}{dt}\right]$$

Define coupling parameters: $\kappa_{ij} \equiv Y_{ij}/G_L$

Broadband condition:

$$\frac{\omega_i}{2Q}\sum_{j=1}^{N}\frac{\partial \kappa_{ij}}{\partial \omega}\frac{A_j}{A_i} \ll 1$$

$$\frac{dA_i}{dt} = \frac{\mu\omega_i}{2Q}S_i(A_i)A_i - \frac{\omega_i}{2Q}\sum_{j=1}^{N} A_j \,\mathrm{Re}\left\{\kappa_{ij}\, e^{\jmath(\theta_j - \theta_i)}\right\}$$

Leads to: ⟶

$$\frac{d\theta_i}{dt} = \omega_i - \frac{\omega_i}{2Q}\sum_{j=1}^{N}\mathrm{Im}\left\{\kappa_{ij}\frac{A_j}{A_i}e^{\jmath(\theta_j - \theta_i)}\right\}$$

UC SB
University of California, Santa Barbara

MAR 5 1996

New Beam-Scanning Method

Conventional:

- Difficult, expensive to make
- Low-yield fabrication
- Requires high-power source
- Tough to monolithically integrate entire system



Coupled-Oscillator Arrays:

- No phase shifters !!
- Only two controls lines for scanning
- Distributed solid-state source: no feed network
- Ideal for low-cost, hand-held or mobile applications



UC SB University of California, Santa Barbara

Arbitrary Coupling Network

Enforce node coditions:

$$Y_{\text{osc},i}(\omega, V_i) + Y_{\text{circ},i}(\omega, \overline{V}) = 0$$
$$i = 1, 2, \ldots N$$



Convert to dynamic equations (Kurokawa):

$$\omega \Rightarrow \left[\omega_i + \frac{d\phi_i}{dt} - \jmath \frac{1}{A_i}\frac{dA_i}{dt}\right]$$

Define coupling parameters: $\kappa_{ij} \equiv Y_{ij}/G_L$

Broadband condition:

$$\frac{\omega_i}{2Q}\sum_{j=1}^{N}\frac{\partial \kappa_{ij}}{\partial \omega}\frac{A_j}{A_i} \ll 1$$

$$\frac{dA_i}{dt} = \frac{\mu\omega_i}{2Q}S_i(A_i)A_i - \frac{\omega_i}{2Q}\sum_{j=1}^{N} A_j \,\mathrm{Re}\left\{\kappa_{ij}\, e^{\jmath(\theta_j - \theta_i)}\right\}$$

Leads to: ⟶

$$\frac{d\theta_i}{dt} = \omega_i - \frac{\omega_i}{2Q}\sum_{j=1}^{N}\mathrm{Im}\left\{\kappa_{ij}\frac{A_j}{A_i}e^{\jmath(\theta_j - \theta_i)}\right\}$$

UC SB
University of California, Santa Barbara

Tightly Coupled Patch/Oscillator Arrays

MAR 13 1996

- Strongly-coupled array
- broadband coupling network
- fabricated on er=10.8 substrate
- 4GHz, d=0.3 λ_0
- Optimum power/efficiency design: 43% Class AB



MAR 25 1996

UC SB

Scanning Measurements

6 x 1 MESFET Array Prototype with patch antennas

4GHz optimum efficiency oscillator design **(43% DC-to-RF conversion)**

Results:

- **Continuous scanning from -40° to +40° off broadside**
- **accomplished by adjusting end-element frequencies (drain bias)**

Excellent correlation with theory







MAR 05 1996

UC SB
University of California, Santa Barbara

Linear VCO Array

8 x 1 MESFET VCO Array Prototype
Varactor-tuned patch antennas

1 Watt output at 8.4 GHz
(10 Watt Effective Radiated Power)

Results:
- Simpler operation due to VCO, possibility of computer control
- **Continuous scanning from -15° to +30° off broadside**

Excellent correlation with theory







MAR 05 1996

UC SB
University of California, Santa Barbara

Improved Scanning Oscillator System



- doubled output greatly increases scan range: doubles inter-element phase shift for a given tuning. Theoretically full hemispherical coverage.
- doublers simplify oscillator design for given output frequency
- amplifier array for best efficiency, also simplifies oscillator design
- low phase noise by locking to stable reference

UC SB
University of California, Santa Barbara

Enhanced Scan Angle

Array

- MESFET/PATCH oscillator array operating at 4GHz doubled to 8GHz
- $\lambda/2$ antenna spacing at 8GHz



Measured Results

- Beam was steered from -40° to +40° through VCO tuning
- Maximum inter-element phase shift attained (after frequency doubling) is +/-133°



MAR 1996

UC SB
University of California, Santa Barbara

Coupling 2D Oscillator Arrays

Couple rows together vertically at edge elements



MAR 05 1996

UC SB
University of California, Santa Barbara

Results for 6 x 2 array

1.7 kW for 6x3 array

- 933 Watt Effective Radiated Power (EIRP)
- Estimated directivity of 81 (19 dB) from pattern measurements (theory predicts 64)
- Leads to total radiated power = **11.7 Watts** 1 W/element
- Array draws 9 Amp @ 8.5 V = **15% efficiency** (wall plug) (includes all bias circuitry)
- Axial ratio <-25dB within HPBW →



MAR 05 1996

UC
University of California, Santa Barbara
SB

300GHz Schottky-Contact RTD Array



MAR 05 1996

UC SB
University of California, Santa Barbara

Circuit Layout of Planar Amplifier Array Using Folded-Slot Antennas



- The bandwidth is wider because the extra slot tends to cancel the off resonace reactance of a single slot.

- Broadband (DC - 4GHz) resistively feedback amplifier design.

  GaAs MESFET, NE32184A

  $Z_{in} = Z_{out} = 125\Omega$

  8dB gain @ 4GHz

- Input impedance of folded-slot antenna is estimated from Babinet's principle.

  $Z_{folded-slot} \approx 125\Omega$

Folded-slot antennas are attractive for active arrays because they are simple to make (one mask step) and can be easily integrated with three-terminal devices (HEMT and HBT).

MAR 05 1996

UC SB
University of California, Santa Barbara

Finite-Difference Time-Domain (FDTD) Method

Why FDTD technique ?

- Flexibility --- suitable for various circuit configurations.
- Active and nonlinear lumped elements can be included.
- Easy programming.



MAR 05 1996

UC SB
University of California, Santa Barbara

Comparison Between Measurement and FDTD Simulation Results



Thickness = 0.787mm $\varepsilon_r = 2.2$



- **Excellent agreement between simulation and measurement.**
- **Great flexibility of analyzing different circuit configurations.**

MAR 05 1996

UC SB
University of California, Santa Barbara

Steady State Field Distributions in the Triple Folded Slot Antenna



Plan view of the antenna



- Fields in three slots are in phase as expected.
- FDTD is a great visual tool for electromagnetic problems.

MAR 05 1996

UC SB
University of California, Santa Barbara

Impedance Scaling using Multiple Slots

Dipole

Half-wave dipole :



$Z_{dipole} \approx 70\Omega$

Folded dipole :



$Z_{in} = 4Z_{dipole} \approx 300\Omega$

N-element folded dipole :

$$Z_{in} = N^2 Z_{dipole}$$

Slot

Half-wave single slot :



$Z_{slot} \approx 500\Omega$

Folded slot :



$Z_{in} = Z_{slot}/4$

N-element folded slot :

$$Z_{in} = Z_{slot}/N^2$$

MAR 25 1996

UC SB
University of California, Santa Barbara

Impedance Scaling Using Multiple-Slot Antennas





FDTD simulation

$\varepsilon_r = 9.8$



Measurement

Frequency Range :
5 GHz to 15 GHz
0.635 mm Alumina substrate

Notes :

The resonant frequencies of these four antennas are about the same.

MAR 05 1996

UC SB

4 x 4 HBT Amplifier Array







- 4x4 HBT array @ 10 GHz
- 0.635 mm Alumina substrate
- 50 Ω five-slot antennas, no matching
- 8 dB gain with ~ 5 % bandwidth

MAR 05 1996

UC SB

Bilateral Injection-Locking Approach

"Mutual Synchronization"
"Inter-Injection-Locking"



Oscillators coupled through some electromagnetic coupling circuit:

- mutual coupling between antennas
- cavity coupling
- transmission-lines circuits

Plane Wave Amplifier Chip

Version Using Folded Slot Antenna

MAR 05 1996



Rockwell

Science Center

UC SB
University of California, Santa Barbara

Preliminary Measured Results of the Amplifier Array

2 x 5 Array

Bias conditions : V_{be} = 1.5V, I_b = 2mA
V_{ce} = 3V, I_c = 30mA



——— Bias on ----- Bias off

- **The on/off ratio is greater than 15dB from 37GHz to 40GHz.**
- **The 3dB bandwidth is close to 3GHz.**

MAR 05 1996

What has limited our progress

- low power, packaged devices (limited performance)
- lack of access to monolithic fab
- scope of problems addressed, frequencies

→ no "kick-ass" result yet
∴ limited funding & global interest

Some directions

- amplifier arrays – natural place for industrial involvement, 6.1 → 6.2 or 6.3
- stronger interaction between systems – device – circuit people
- better guidance from Gov't/industry as to potential applications/frequency ranges
- universities continue doing "new" things

MAR 05 1996

QO Technology Survival Path

- Based on the opinion of several experts, a realistic challenge for quasi-optical technology is a proof-of-principle power amplifier module that would provide an evidence of high power amplifications at millimeter-wave frequencies. Such a demonstration may ensure a suitable market place for this emerging technology, perhaps at first as a replacement for high volume conventional "fixed phase" power source, such as TWTs used in Ka and W-band missile seeker systems.
- Prior to building a huge infrastructure for QO technology, perhaps it is ideal for ARPA to support a single QO industrial program (~2 years) for establishing a proof-of-principle for QO technology. Under such a program, the QO Technology Survival would be depend on its demonstrated merits.
- Compact's QO Mission:
  - Develop a set of *commercially available* modeling and analysis tools to support the design and development of quasi-optical systems.
  - Through our " QO CAD alliance members", we possess a significant source of uncommercialized quasi-optical CAD tools and techniques. This will enable us to develop cost effective CAD products through "shared development and resources".

COMPACT SOFTWARE

HEWLETT PACKARD HEWLETT PACKARD HEWLETT PACKARD

rayork@ece.ucsb.edu

MAR 05 1996

UC SANTA BARBARA

- coupled oscillator systems & modelling
- Novel scanning concepts
- integrated antenna design
- antennas for arrays
- modelling of arrays & grids using FDTD
- amplifier arrays
- Quasi-optical distributed circuits

conventional antennas vs. grids

supported by ARO, NSF, Rockwell Science Center, Hughes Research Laboratories, Jet Propulsion Lab

MAR 05 1996


Electromagnetics:
• antenna modelling
• antenna-circuit interactions
• beam guiding system
• packaging
GaAs
InP
epi-transfer
GaN?
Device technology:
• yield & uniformity over large areas
• substrates (affects antennas and thermal issues)
• device size
Economics:
• Frequency range?
• Does QOA solve the problem?
• Hybrid vs. monolithic
Quasi-Optical Arrays
Circuit Design:
• efficiency and array size (total output power)
• array topology
• systems requirements
Nonlinear. Dynamics chaos
Thermal design:
• efficiency and array size (total output power)
• array topology

MAR 1996

Quasi-Optical Research

at the University of Colorado

Zoya Popović

Associate Proffessor, Electrical Engineering
UNIVERSITY OF COLORADO, BOULDER

Students:

Scott Bundy*
Tom Mader*
Jon Schoenberg*
Wayne Shiroma
Milica Markovic
Jon Dixon
Stein Hollung
Eric Bryerton
Michael Forman
Joe Tustin
Robert Brown

Funding:

NSF
ARO
Lockheed Martin
Compact Soft.(Air Force)
Compact Soft.(ARPA)
NAWC, China Lake
CAMI, ETAP
MURI (U of M)
SCT (Air Force)

* now with SCT, Inc., Golden, CO
* now with Hughes, El Segundo
* now with Phillips Airforce Labs, Albaquerque

MAR 05 1996

Recent advances in quasi-optics at the University of Colorado 1994 and 1995, *Zoya Popović*

Amplifiers:

- 24-element patch lens amplifier transmitter, 9 dB absolute power gain, 10 GHz.
- 24-PHEMT lens amplifier receiver with 2-stage LNAs, 13 dB gain, 1.9 dB noise figure, 30 dB isolation, 10 GHz.
- 4-MESFET high-efficiency power amplifier array, 2.4 W at 5 GHz, 74% drain eff., 64% PAE, 84% power-combining eff.
- Design of 2-Watt Ka-band array (with Lockheed Martin, Orlando).
- Monolithic 60-GHz HEMT array (with Lockheed Martin, Baltimore).
- Multistage lens amplifiers, X-band.

Oscillators and mixers:

- Three-dimensional grid oscillators, 100 HEMTs in 4 grids at 5 GHz.
- Dual-frequency grid oscillator using an electronically tunable frequency selective surface, 4 and 6 GHz.
- Design of 36-MESFET Ka-band high power hybrid oscillator (with NAWC, China Lake).
- Design of monolithic 100-HEMT Ka-band oscillator (with TLC, SBIR I and Honeywell).
- Grid oscillators as self-oscillating mixers, 5 and 10 GHz, 100-800 MHz IF.

Other components:

- Linear-to-circular polarizer, X-band, 1.1 dB loss, 1.2 dB axial ratio.
- Isolator, X-band, -19 and 9 dB isolation for the V and H components.
- Digital phase modulators, X-band, 0-90 and 0-180 deg in transmission.
- Electronically-tunable partially transparent reflector (FSS), 30% tuning, transmission 0.1 to 1 from 2 to 10 GHz.

Subsystems:

- Two-stage power combining with 28-HEMT grid oscillator feeding a 24-HEMT lens amplifier, X-band.
- Beam steering, beam forming and beam switching with lens amplifier.
- Receiver with lens amplifier and grid subharmonic self-oscillating mixer, C-X band.
- Angular diversity with a receiving lens amplifier, X-band, -30 to 30 deg.

Quasi-Optical Amplifier Feed Techniques

MAR 5 1996







C U

Quasi-Optical Group

MAR 15 1996



MAR 05 1996

Absolute Gain and Isolation for 24-Element CPW LNA Lens Array



3 dB BW = 11%

ISOLATION > 25d

Noise Figure and Associated Gain for 24-Element CPW LNA Lens Array, Low Bias



NF_{min} = 1.9 dB @ 9.8 GHz

G_{Assoc} = 11.8 dB

MAR 05 1996

The Quasi-Optical Class-E Power Amplifier



Single Element:
0.7W @ 5 GHz
PAE = 70%

2x2 Array: 2.4W, 64%

- No vias
- No lumped elements
- Good heat sinking
- Polarization isolated
- Broadband structure

~ 80% POWER-COMBINING EFFICIENCY

Quasi-Optical Group

MAR 15 1996

Harmonic Balance Circuit Simulations Using an Ideal Switch Model at 5 GHz





MAR 05 1996


300
250
200
150
100
50
Power (mW)
50
40
30
20
10
0
Efficiency (%)
Power
Efficiency
0
1
2
3
4
5
Number of Grids


100
90
80
70
60
50
Combining Efficiency (%)
0
1
2
3
4
5
Number of Grids

Tunable Transmission Filter





30% tuning bandwidth

MAR 15 1996

Mode-Selective Grid Oscillator



Unlocked spectrum with two competing modes



Locked mode achieved through gate bias adjustment



Unlocked spectrum with a partially reflecting front mirror



Locked mode achieved using a variable-reflectance mirror

MAR 1996

Quasi-Optical Isolator

MAR . . 5 1996





f = 8.93 GHz

↑ Isolation 9dB

→ Isolation 19dB



MAR 25 1996


0
-5
-10
-15
-20
-25
NORMALIZED POWER, dB
0
15
30
-90
-45
0
45
90
ANGLE FROM BROADSIDE, DEG


Grid Oscillator #2
θ
Optical Axis
E-Plane Focal Arc
Grid Oscillator #1
H-Plane Focal Arc
Lens Amplifier
θ
Output
Main Lobe(s)

MAR 1996

Quasi-Optical Group

MAR 15 1996



Quasi-Optical Receiver with Angle Diversity

MAR 15 1996



n uncorrelated beams:

$$P_e \propto \left(\frac{n}{S/N}\right)^n$$


0
-5
-10
-15
-20
Relative IF Power (dB)
-90
-45
0
45
90
Scan Angle (degrees)
-30 deg. position
0 deg. position
+30 deg. position

MAR 05 1996



Millimeter-wave Wireless Laboratory

MAR 1996

Quasi Optical Arrays for Millimeter-Wave Communication Applications

RICHARD COMPTON

SCHOOL OF ELECTRICAL ENGINEERING

CORNELL UNIVERSITY

ITHACA NY 14853

HTTP://WRG.EE.CORNELL.EDU/



Millimeter-wave Wireless Laboratory

Outline

MAR 05 1996

1. Applications
   - PCS, MMDS, LMDS, 60 GHz, (Point-to-Point)
   - Digital Battlefield
2. Key Technical Parameters
   - Power/Filtering/Spectral Efficiency/Mechanical Design
3. Quasi-Optics
   - Circular Arrays/Reflectors/Diversity
   - Modulation FSK/PSK
4. Technology Barriers
   - Design/Measurement
   - Low-Cost Manufacture
5. Research Strategies

TELECOMMUNICATIONS

Cable Television Without The Wires

A 5-in. antenna receives the microwave signal.

BY STEPHEN A. BOOTH, Contributing Editor
PM Photo by J.R. Rost

MAR 1996

MAR 15 1996

Local Multipoint Distribution Service (LMDS)



MAR 13 1996



MAR 1996

Power Requirements

75 MBPS 60GHz 10 Watt Transmitter

Hub Transmission	10	dBW
Transmit Antenna Gain	12	dB
Path Loss (100m)	-108	dB
Noise Figure	-6	dB
Receive Antenna Gain	6	dB
Received Power	-86	dBW
Noise (50MHz)	-127	dBW
C/N	41	dB
Required C/N	15	dB
Fade Margin	26	dB

MAR 15 1996

Filtering



MAR 05 1996

Thermal Control





MAR 15 1996

Spectral Efficiency





$$V(t) = I(t)\sin\omega t + Q(t)\cos\omega t$$

MAR 15 1996

Quasi-Optical Arrays



Coupled Oscillator Array



Distributed Grid Array

MAR 1996

Circular Array



MAR 15 1996

Array Pattern



MAR 15 1996

Pattern Enhancement



MAR 05 1996

Reflector Enhancement





MAR 05 1996

Reflector Enhancement



MAR 05 1996

Diversity



MAR 05 1996

QPSK Modulator



MAR 25 1996

Non-Linear Modelling



MAR 05 1996

Measurement Layout



Measurement

MAR 05 1996





MAR 15 1996

Research Strategies

1. System Level Evaluation of Quasi-Optics
   - — Broadband Trial
2. Industry/University Program
   - — Service Providers (Cable/RBOC)
   - — Equipment Manufacturers
   - — Microwave Companies
   - — University
     - — Coding
     - — VLSI
     - — RF Circuits and Devices

MAR 05 1996

Quasi Optics
Two Technology Breakthroughs

Power



- Solid State Sources from Tens of watts to Thousands of watts
- Microwave and Millimeter Wave Bands
- Gracefully Degrading
  High Power with Solid State

Phased Arrays



- Wafer Scale Integration of Simple Identical Circuit Cells
- 16 : 1 to 3000 : 1 Reduction in Module Count
- Lower Cost by 3 to 10 Times
- Upper Microwave and Millimeter Wave Bands

  Enables Phased Arrays at MMW

MARTIN MARIETTA

SA093-0238-02

MAR 05 1996

MMW Quasi-Optic Power Applications

Area	Example Programs	Bands	Power Watts	Prod Nrs	When
Smart Weapons	Longbow, JDAM P3I, BAT, LOCAAS, Guided Projectiles, MSTAR	Ka, W	2-20	10,000's	'95-'05
Hit-to-Kill Seekers	Erint/PAC3, JSSAM, Corps SAM, Helo A/A, ADKEM, HARM	Ku, Ka, W	50-2000	1,000's	'00-'10
All Wx Rot Wing Strk/Recce	AH-64, AH-66, SH-60, OH-58	Ka, W	10-100	100's	'95-'05
All Wx Fixed Wing Strk/Recce	F-15, F-16, F-18, F-117, B-1, B-2	Ku, Ka	> 1000	100's	'00-'10
Ground FCR	M1, M2, CIWS upgr, Base Def	Ka, W	50-200	100's	'00-'10
Comm	Xlinks, Downlinks, Uplinks	Kt, Q, V	5-500	1,000's	'00-'10

MAR 15 1996

Grid Array Power Availability

Versus Frequency and Side Length



Lockheed Martin Proprietary

LOCKHEED MARTIN

MAR 1996

6 by 6 Array with 3 by 3 Amplifier and Polarizer in Test Fixture

MAFET



COMPETITION SENSITIVE

Measured Results



Amplifier Array (Spillover and Reflected Losses Removed)		
	Small Signal	Large Signal
Gain	14 dB	7 dB
Power output		2.5 watts
Amplifier Array withTest Fixture Losses		
	Small Signal	Large Signal
Gain	6 dB	- 2 dB
Power output		1 watt

V-Band Monolithic PHEMT Grid Amplifier

(Lockheed Martin and Cal Tech)

- 36 elements at 50 GHz center frequency
- 5 dB net gain measured (May, 1995)
- 27 dB on/off ratio



36 Element
Grid Array



Single Cell
Design

LOCKHEED MARTIN

Key Elements of Amplifier Tested

MAR 05 1996

Uniform Illumination



Intra- Array Coupling



Inter- Array Coupling



Gain

Input



Output



First Amplifier Array



Second Amplifier Array



Third Amplifier Array

Power

Lockheed Martin Proprietary

LOCKHEED MARTIN

Constrained Package Amplifier Results

MAR 25 1996



	Parameter	Value
	Frequency	X-band
	Array Size	9 elements
Hard Horn Feed	Power out	90 mw
	Total Gain	14.2 dB
	PAE	10.5%*
	Drive Power	+ 5 dBm
	Horn Pair Loss	2.2 dB
Regular Horn Feed	Power out	30 mw
	Total Gain	14.7 dB
	PAE	5.4%
	Drive Power	0 dBm
	Horn Pair Loss	1.4 dB

Results courtesy of Dr. A. Mortazawi, Univ. Central Florida

* Efficiencies as high as 16.5% and power over 100 mw measured under different conditions; second stage efficiency was 25%

LOCKHEED MARTIN

MAR 05 1996

Key Results

Key Element	Yr	Development	Results
Monolithic Grid Arrays	95	Separate PHEMT and HBT amplifier arrays tested by Cal Tech (50 Ghz & 40 GHz)	**4dB/3dB gains** measured in far field
Amplifier Cells	94	2 stage cascaded MESFET cells tested in 9 element hybrid array	**12- 17 dB gain** (small signal) at 35 GHz
RF Power	95	Saturated RF Power Measurements at Ka Band with 6 element array	**2.5 watts** density measured far field
Quasi-optics Feed	95	Hard Horn concept tested at X Band and modeled at Ka Band	**1 dB uniformity** over array; 4.6 dB improved output over gaussian
Constrained Package	95	9 element X Band array tested in closed hard horn package	Far field/constrained package gains match; **PAE in high teens**
Close Coupling	94	Intra- and inter- grid coupling concepts tested with just " mils" of coupling thickness	**Low loss** (<.5 dB); wide band (>20%); low VSWR (>20 db isolation)
Liquid Cooling	94	Liquid cooling test at MMC	Demo 50 watt capacity
Cooling	95	Coupling through ground planes	Metal grd planes permit **conduction cooling**

MAR 05 1996

QUASI-OPTICS POWER AMPLIFIER CHARACTERISTICS
CURRENT AND PROJECTED

Frequency Band (GHz)	Output Power (watts)	Net Volume (cu. in.)		Weight (oz.)		P.A. Efficiency (%)	
		Now	Future	Now	Future	Now	Future
Ka	20	5	3	16	6	15-20	25-30
Ka	100	20	10	40	16	15-20	25-30
W	5	4	2	10	4	10-15	20
W	50	15	8	50	12	10-15	20

Legend

Gain: 10-12 dB
Duty: 25%
BW: > 1 GHz

MAR 5 1996

GRID AMPLIFIERS

David Rutledge, Caltech

- Hybrid 10-GHz pHEMT 3.7-W grid amplifier—
  Michael DiLisio and Scott Duncan, Lockheed-Martin
- Monolithic 40-GHz HBT 650-mW grid amplifier—
  Jeff Liu and Emilio Sovero, Rockwell Science Center
- Monolithic 44–60 GHz pHEMT grid amplifier—
  Michael DiLisio and Sandy Weinreb, Lockheed-Martin

MAR 1996

A Grid Amplifier



Cross-polarized input and output.

Provides good isolation

Allows indepenent tuning of input and output circuits through metal-strip polarizers

MAR 1996

GRID AMPLIFIERS

David Rutledge, Caltech

- Hybrid 10-GHz pHEMT 3.7-W grid amplifier—
  Michael DiLisio and Scott Duncan, Lockheed-Martin
- Monolithic 40-GHz HBT 650-mW grid amplifier—
  Jeff Liu and Emilio Sovero, Rockwell Science Center
- Monolithic 44–60 GHz pHEMT grid amplifier—
  Michael DiLisio and Sandy Weinreb, Lockheed-Martin

MAR 5 1996

Grid Amplifier Unit Cell



10 GHz 10 × 10
0.1 μm pHEMT

Arrows indicate direction of rf current.

MAR 15 1996

Assembled Grid Amplifier



Transmission-line Equivalent Circuit at 9GHz



Caltech

MAR 1996

Grid Amplifier Gain Curves

Amplifier tuned to 9GHz.



Peak gain 12dB at 8.9GHz.

3-dB bandwidth of 1.3GHz (15%).

Caltech

MAR 1996

Grid Amplifier Power Saturation

Amplifier tuned to 9GHz to match TWT output



3.7W saturated output power

MAR 1996

Grid Amplifier Noise Figure

10GHz amplifier with output tuner



Oscillation suppression gate resistors probably increase noise figure.

Caltech

MAR 05 1996

Angular Dependence



Grid Amplifier
(Output tuner removed)



Theoretical curves generated by scaling transmission line lengths by $\cos\theta_i$ and TE impedances by $\sec\theta_i$ and TM impedances by $\cos\theta_i$

MAR 05 1995

Angular Dependence



Grid Amplifier
(Output tuner removed)



Theoretical curves generated by scaling transmission line lengths by $\cos\theta_i$ and TE impedances by $\sec\theta_i$ and TM impedances by $\cos\theta_i$

Caltech

MAR . . 5 1996

100-Element pHEMT Grid Amplifier

Chips fabricated by Lockheed Martin Laboratories, Baltimore

Summary of Results

- Gain and stability models developed and verified.
- Grid constructed using Martin Marietta 0.1-um pHEMT's.
- Spurious common-mode oscillations suppressed with chip resistors in the gate leads.
- Measured gain of 10dB at 10GHz and 12dB at 9GHz.
- 15% 3-dB bandwidth at 9GHz.
- Accepts beams with incidence angles up to 30°.
- Measured minimum noise figure of 3dB at 10GHz.
- 3.7W maximum saturated output power at 9GHz.
- Peak power-added efficiency of 12% at 9GHz.
  Peak device efficiency of 20%.

Caltech

MAR 05 1996

Grid Amplifier Output Radiation Pattern

H-plane pattern of grid tuned for 10GHz without output tuner.

Normally-incident input.



Theoretical pattern assumimg uniform array of 10 elemntary dipoles spaced 7.3mm apart.

Measured pattern is diffraction-limited.

MAR 05 1996

GRID AMPLIFIERS

David Rutledge, Caltech

- Hybrid 10-GHz pHEMT 3.7-W grid amplifier—
  Michael DiLisio and Scott Duncan, Lockheed-Martin
- Monolithic 40-GHz HBT 650-mW grid amplifier—
  Jeff Liu and Emilio Sovero, Rockwell Science Center
- Monolithic 44–60 GHz pHEMT grid amplifier—
  Michael DiLisio and Sandy Weinreb, Lockheed-Martin

MAR 05 1996

Rockwell HBT Layout



Monolithic Grid Amplifier

SCP.0816A.041395

MAR 05 1996



CALIFORNIA INSTITUTE OF TECHNOLOGY

Rockwell

Science Center



MAR 05 1996

Rockwell

Science Center

MAR 05 1996

Caltech

Monolithic HBT Grid Amplifier
Gain Response



Gmax: 5 (dB) @ 40 (GHz)
3-dB bandwidth: 1.8 GHz ; 4.5 %

Monolithic HBT Grid Amplifier Output Power vs. Input Power



Max. Output Power: 670 mW

5dB small signal

2.5dB gain (Limited input power)

MAR 05 1996

Caltech

Summary of Monolithic HBT Grid Amplifier

Gain Measurement
G_{max}: 5dB @ 40GHz
3-dB Bandwidth: 1.8GHz ; 4.5%

□

Power Measurement
Maximum Output Power: 670mW
Maximum Power-Added Efficiency: 4%

MAR 05 1996

GRID AMPLIFIERS

David Rutledge, Caltech

- Hybrid 10-GHz pHEMT 3.7-W grid amplifier—
  Michael DiLisio and Scott Duncan, Lockheed-Martin
- Monolithic 40-GHz HBT 650-mW grid amplifier—
  Jeff Liu and Emilio Sovero, Rockwell Science Center
- Monolithic 44–60 GHz pHEMT grid amplifier—
  Michael DiLisio and Sandy Weinreb, Lockheed-Martin

MAR 05 1996



Caltech

MAR 05 1996

Grid Amplifier Gain Curves

Amplifier tuned to 48GHz.



Peak gain 6dB at 48GHz.

3-dB bandwidth of 1.7GHz (3.5%).

MAR 05 1996

Grid Amplifier Tuning Range



44-60GHz tuning range.

Output tuner used for 60GHz gain curve.

Caltech

MAR 15 1996

36-Element Monolithic pHEMT Grid Amplifier

Grids fabricated at Lockheed Martin Laboratories, Baltimore

Summary of Results

- Grid constructed with Lockheed Martin 0.1-um pHEMT's.
- Grid can be tuned by changing polarizer/tuner positions. Measured gain of 6.5dB at 44GHz and 2.5dB at 60GHz.
- 6% 3-dB bandwidth at 54GHz.
- Gain reduced by 5dB—possibly due to diffraction losses from the small grid ($\lambda/2$).
- Could be used as a Travelling Wave Tube (TWT) replacement.

MAR 15 1996

GRID AMPLIFIERS

David Rutledge, Caltech

- Hybrid 10-GHz pHEMT 3.7-W grid amplifier—
  Michael DiLisio and Scott Duncan, Lockheed-Martin
- Monolithic 40-GHz HBT 650-mW grid amplifier—
  Jeff Liu and Emilio Sovero, Rockwell Science Center
- Monolithic 44–60 GHz pHEMT grid amplifier—
  Michael DiLisio and Sandy Weinreb, Lockheed-Martin

rayork@ece.ucsb.edu

UC Santa Barbara

- coupled oscillator systems & modelling
- Novel scanning concepts
- integrated antenna design
- antennas for arrays
- modelling of arrays & grids using FDTD
- amplifier arrays
- Quasi-optical distributed circuits

conventional antennas vs. grids

MAR 15 1996

supported by ARO, NSF, Rockwell Science Center, Hughes Research Laboratories, Jet Propulsion Lab.


Electromagnetics:
• antenna modelling
• antenna-circuit interactions
• beam guiding system
• packaging
GaAs
InP
epi-transfer
GaN?
Device technology:
• yield & uniformity over large areas
• substrates (affects antennas and thermal issues)
• device size
Economics:
• Frequency range?
• Does QOA solve the problem?
• Hybrid vs. monolithic
Quasi-Optical Arrays
Circuit Design:
• efficiency and array size (total output power)
• array topology
• systems requirements
Nonlinear Dynamics chaos
Thermal design:
• efficiency and array size (total output power)
• array topology
MAR 05 1996